

WOOD FLOOR OIL ENVIRONMENT SPECIAL MAINTENANCE



**NEW!
NO NEED TO
BUFF!**

Combines high Performance and Environmental Friendliness (Please consult the Environmental Data Sheet)

•
Odourless

•
European Eco-label

•
Dries within 30 minutes

•
Preserves and maintains the natural finish of Wood Floor Oil Environment

•
Quick and easy maintenance and refinishing

•
slip resistant

•
European Toy Safety Standard EN 71.3

NO BUFFING REQUIRED

PRODUCT DESCRIPTION

- Blanchon WOOD FLOOR OIL - SPECIAL MAINTENANCE ENVIRONMENT is the natural complement to Blanchon WOOD FLOOR OIL ENVIRONMENT.
- A real technical innovation, odourless WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE is extremely easy to use and trouble-free. Its technical performance and formulation comply with the most stringent ecological criteria: it contains less than 2% VOC as per Directive 2004/42/CE, complies with the European Eco-label environmental requirements, the European Standard EN 71.3 and is both user-friendly and environmentally-friendly.
- Simple and practical, WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE may be applied directly to clean wood treated with WOOD FLOOR OIL ENVIRONMENT: no buffing is required by hand or with a buffing machine to care for or touch up parquets and wood floors.
- The area can be reused very quickly thanks to its odourless, easy-to-use, fast-drying formula.
- WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE gives long-lasting dust-proofing and is available in a natural finish (colourless).

SUBSTRATE PREPARATION

- WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE is specially designed to maintain parquets and wood floors treated with WOOD FLOOR OIL ENVIRONMENT.
- WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE should be applied on a clean, dry floor: sweep or vacuum the floor to remove all traces of dust before applying.
- Small stains and marks can be easily removed with Blanchon NATURAL SOAP FOR OILED WOOD FLOORS or a neutral detergent (using a well wrung-out cloth or mop, never a soaking wet one). NB: Wait 7 to 10 days before applying for the first time to give WOOD FLOOR OIL ENVIRONMENT time to fully harden.
- Stubborn dirt, stains or scratches can be removed by fine sanding. WOOD FLOOR OIL ENVIRONMENT should then be re-applied to this area.

Important: maintaining wood treated with stained WOOD FLOOR OIL ENVIRONMENT (or previously stained wood) requires particular care and regularity to avoid changes in the shade

NB: Refer to the Routine Cleaning section on the next page.

DIRECTIONS FOR USE

- WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE should be applied as soon as the wood floor impregnated with WOOD FLOOR OIL ENVIRONMENT loses its natural finish (normal wear and tear, minor scratches, etc.).
- Ready to use: do not dilute. Shake well before and during use. Do not apply if the temperature is below 12°C. Only use in well-ventilated areas. Do not leave plants and aquariums in contact with the solvent vapours.
- Perfect adhesion on clean, dust-free, dry wood oiled with WOOD FLOOR OIL ENVIRONMENT (cleaned with NATURAL SOAP FOR OILED WOOD FLOORS using a well wrung-out mop or cloth: refer to § SUBSTRATE PREPARATION).
- Apply a thin coat of WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE with a microfibre-type mop (or, failing this, with a fine, clean cotton cloth) onto a clean, dry surface. (A spray may be used and the floor immediately wiped with the micro-fibre.) Small, localised areas can be touched up using a cotton cloth to apply and polish.
- The product spreads immediately and does not have to be worked for a long time. The use of a machine (buffing machine with 3 rotating brushes or heavy duty buffing machine with a beige pad) is neither necessary nor recommended.
- Dries within around 30 minutes. The floor can then be used as usual.
- Frequency: Whenever the wood floor loses its beautiful finish, generally once or twice a month under normal conditions of use.
- On high-traffic wood floors, regular maintenance can be reinforced by applying a general coat of WOOD FLOOR OIL ENVIRONMENT (cf. MAINTENANCE and REFINISHING).
- The more WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE is used, the easier maintenance becomes.

A WELL MAINTAINED OILED WOOD FLOOR LOOKS BETTER AND BETTER AS TIME GOES BY

TOOL CLEANING

- Clean tools immediately after use with water.
- Protecting the environment:
 - Wring out cloths and wipe tools thoroughly after application.
 - Rinse with as little water as possible in a recipient and leave this water to evaporate.
 - The residue may then be disposed of normally in a waste bin.
 - Seal container properly after use.
 - Do not pour down the drain.

Blanchon

DRYING

- Dust free: Around 5 minutes.
- Light traffic: 30 minutes under normal conditions. Take reasonable precautions during the first hour following application.
- Protect the floor using felt guards underneath table and chair legs. If necessary, a good quality mat placed at the entrance will retain dust and grit. Wipe down any water or other liquid spillages immediately and take particular care with flower pots. Do not move heavy furniture around. Remove dust with a vacuum or broom: do not use impregnated fabrics.

COVERAGE

- Around 25 to 35 m² per litre per coat.

STORAGE

- 1 year in the original unopened container. Protect from frost: take care if storing in vehicles.
- Seal the container properly after use.
- Refer to the relevant Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com).

MAINTENANCE & REFINISHING

- **Routine cleaning:** Vacuum, or mop using NATURAL SOAP or neutral detergent with a well wrung-out mop or cloth.
- **Regular maintenance:** Apply WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE with a microfibre-type mop (or with a clean, fine cotton cloth) on a clean, dry surface.
- **Refinishing small areas:** Sand the damaged areas vigorously using fine-grade sandpaper before applying 1 or 2 thin coats of WOOD FLOOR OIL ENVIRONMENT - SPECIAL MAINTENANCE with a clean, fine cotton cloth. For a perfect finish, treat the whole surface as described in **Regular Maintenance** above.
- **Refinishing large areas:** Sand the whole surface, remove dust and then apply a thin coat of natural or coloured WOOD FLOOR OIL ENVIRONMENT using a roller.

TECHNICAL DATA

USE	OIL FOR WOOD FLOORS, PARQUETS AND WOOD
RESIN TYPE	Water-based oils
AFNOR CLASSIFICATION	Family 1, class 7b2
DENSITY	1.01 (at 20°, as per NF T 30020)
REGULATORY INFORMATION	Refer to the relevant Safety Data Sheet (also available on www.blanchon.com or www.quickfds.com)
FLUIDITY	35 seconds (ISO Cup n°2.5, at 20°C)
RESISTANCE TO HOUSEHOLD PRODUCTS	Vegetable oil, mustard, ketchup, vinegar, water, coffee, tea, normal household detergents, 40° alcohol, ink, diluted bleach: no adverse affects found (after 20 days' drying, as per NF T 30053).
SURFACE MOISTURE	NA

APPENDIX 1: REGULAR CLEANING OF OILED WOOD FLOORS

- Clean with a damp mop using Blanchon NATURAL SOAP FOR OILED WOOD FLOORS (250 ml diluted in 10 litres of water).
- Work on one area at a time, rinsing the cloth or mop regularly: it should always be well wrung out to avoid getting the wood floor too wet.
- Frequency: From once a week on light-traffic floors to daily cleaning on heavy-traffic floors.
- Wipe up any water spillages immediately on floors treated with WOOD FLOOR OIL ENVIRONMENT.

*Appendix 2: REFINISHING

- **REFINISHING SMALL AREAS:** For small areas with specific damage (cigarette burns, impact damage, etc.) rub or scrape to remove the damage and then apply WOOD FLOOR OIL ENVIRONMENT- SPECIAL MAINTENANCE. This is one of the great advantages of a wood floor treated with WOOD FLOOR OIL ENVIRONMENT.
- **REFINISHING LARGE AREAS:** On oiled wood floors that have not been cared for as frequently as their use requires, a general sanding can be done using a buffing machine fitted with a sanding disc (about 120 grit) before applying a coat of undiluted WOOD FLOOR OIL ENVIRONMENT (using a short-haired roller).

EUROPEAN ECO-LABEL 

This label is awarded to interior paints and varnishes which comply with the environmental requirements laid down by the European Union's ecological label scheme. Registration N°FR/7/11

- Good results for interior use
- Limited use of dangerous substances
- Low in solvents

For more information on the EU ecological label, please consult the Web site <http://europa.eu.int/ecolabel> or contact AFAQ-AFNOR Certification 11 Av. Francis de Pressensé 93571 ST DENIS LA PLAINE Cedex

Technical Data Sheet issued by the Documentation Department on 08.12.2005 and validated by the Technical Department on 08.12.2005 and the Sales Department on 08.12.2005. Designed and made in France.

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee nor engage our responsibility when our products are used. This Technical Data Sheet cancels and supersedes all previous versions.

BLANCHON S.A. - Société anonyme à directoire et conseil de surveillance au capital de 4 258 258 €
RCS LYON 390 112 886 - APE 243 Z
CCP 196.03 F LYON
E-mail : info.uk@blanchon.com
Site internet : www.blanchon.com



28, rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX (France)
Tél. 04 72 89 06 00
Fax 04 78 70 07 18
Export Direct Lines
Tél : (0033) 472 89 06 09
Fax : (0033) 472 89 06 02